

OPTI 544: Problem Set 7
Posted April 10, Due April 18

Electronic Submission Only, by email to Jon Pajaud (jpajaud@email.arizona.edu)

I

Consider the x -polarized electromagnetic field in a cylindrical cavity of length L and cross sectional area A . Using the standard normal mode expansion of $E_x(z,t)$ and $B_y(z,t)$ from class, write down expressions for the Hamiltonian and the Lagrangian in terms of the generalized coordinates $q_j(t)$ and their time derivatives.

- (a) Use the Lagrange equations of motion to derive a second order differential equation for the $q_j(t)$'s. [11] [SEP]
- (b) Substitute the normal mode expansion of $E_x(z,t)$ in the wave equation and derive a second order differential equation for the $q_j(t)$'s. Compare to the result in (a) above. [11] [SEP]

II

Consider in the following a 4-port beamsplitter with $t = 1/\sqrt{2}$ and $r = i/\sqrt{2}$.

- (a) Let the input state be $|\Psi_{in}\rangle = (\sqrt{1-\varepsilon}|1\rangle_1 + \sqrt{\varepsilon}|2\rangle_1)(\sqrt{1-\varepsilon}|1\rangle_2 + \sqrt{\varepsilon}|2\rangle_2)$.
 - i. e. the wavepackets entering each port are mostly one-photon states but contain a small admixture of two-photon states. Find the output state $|\Psi_{out}\rangle$.

We use photomultiplier type detectors to measure the outputs from the beamsplitter. These detectors will click once when struck by a pulse of one or more photons.

- (b) Find the probability of a coincidence detection as function of the two-photon contamination